

Parametri	VA0090221 Power Unit 540W-230V-PROG-DALI-1_10V-BI
IK-luokka	IK09
Kotelointiluokka	IP66
Ohjaus	On/Off; PROG-DALI; 1_10V ; BI
Suojausluokka	1
Ta-luokka max. (°C)	40
Ta-luokka min. (°C)	-20
Jännite (V)	198 - 264V
Liitäntälaitemäärä	1
Ottoteho (W)	540
Syttymisvirta (A)	15 A ; T=170us @ 230 VAC T=10% Of Ipeak
Taajuus (Hz)	0/50/60
Tasajännite	175-275
Tehokerroin	0,97
Päivitettävyyys	Ei
Runkomateriaali	Ruostumaton teräs (AISI 304)
Arvioitu toimitusaika tehtaalta	8 viikkoa
Asennustapa	Pinta, asennusohjeen mukaisesti
Sertifikaatit	CE
Valmistusmaa	Suomi
Tuotteen korkeus (mm)	220
Tuotteen leveys (mm)	600
Tuotteen pituus (mm)	400
elinikä Ta +25 °C (h)	50000
Takuu	5
Varastointi maks. suht. ilmankosteus %	Non condensing, 5...95 %

Features

CLO	Yes, programmable
AstroDim	Yes, programmable
SwitchDim	Via 220 V on DALI input
Corridor function	Yes, programmable
Additional features	Input voltage measurement, SW upgrades supported via DALI bus
External temperature measurement	External NTC
Circuit Protections	Short and open circuit, overload and cold start protection, Temperature protection (dim when Tc exceeding Tc max)
Approvals for power units inside	CE, RoHS, ENEC CE, RoHS, ENEC

Parameter	VA0090221 Power Unit 540W-230V-PROG-DALI-1_10V-BI
IK Class	IK09
IP Class	IP66
Controlling options	On/Off; PROG-DALI; 1_10V ; BI
Protection Class	1
Ta Class max. (°C)	40
Ta Class min. (°C)	-20
Input Voltage (VAC)	198 - 264V
Power Units	1
Max Power (W)	540
Inrush current	15 A ; T=170us @ 230 VAC T=10% Of Ipeak
Frequency (Hz)	0/50/60
Input Voltage (VDC)	175-275
Power factor (PF) @ maximum load	0,97
Upgradable	Ei
Housing material	Stainless steel (AISI 304)
Estimated delivery time from factory	8 wks
Installation method	Surface installation; according to the installation manual
Sertificates	CE
Manufacturing country	Finland
Product Height (mm)	220
Product Widht (mm)	600
Product Lenght (mm)	400
Lifetime	50000
Warranty	5
Storage humidity range	Non condensing, 5...95 %

CLO	Yes, programmable
AstroDim	Yes, programmable
SwitchDim	Via 220 V on DALI input
Corridor function	Yes, programmable
Additional features	Input voltage measurement, SW upgrades supported via DALI bus
External temperature measurement	External NTC
Circuit Protections	Short and open circuit, overload and cold start protection, Temperature protection (dim when Tc exceeding Tc max)
Approvals for power units inside	CE, RoHS, ENEC CE, RoHS, ENEC